

BETTER BY DESIGN

**UM3
E3/L3**



UM3 E3/L3

All Steel Radial

Reinforced shoulder and Wear
resistant self cleaning tread.

Suitable for all surfaces.

Excellent Traction, manoeuvrability, and flotation.

Reduced Vibration and increased stability.

UM3 E3/L3



maitech®
ALL STEEL RADIAL

SIZE	PATTERN	LOAD INDEX SPEED SYMBOL STAR MARKING	SPEED	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (100 KPA=1BAR) AND SPEEDS														
				KPa	200	225	250	275	300	325	350	375	400	425	450	475	500	525
				psi	29	33	36	40	44	47	51	54	58	62	65	69	73	76
15.5R25	UM3 E3/L3	176A2/160B**	10 Km/h	Kgs						5000	5150	5450	5600	5800	6150	6300	6500	6700
			5 m.p.h.	lbs						11000	11400	12000	12300	12800	13600	13900	14300	14800
			50 Km/h	Kgs	2800	3000	3150	3350	3550	3650	3875	4000	4250	4375	4500			
			30 m.p.h.	lbs	6150	6600	6950	7400	7850	8050	8550	8800	9350	9650	9900			
17.5R25	UM3 E3/L3	182A2/167B**	10 Km/h	Kgs						6000	6150	6500	6700	7100	7300	7500	7750	8000
			5 m.p.h.	lbs						13200	13600	14300	14800	15700	16100	16500	17100	17600
			50 Km/h	Kgs	3075	3350	3650	3875	4125	4375	4625	4750	5000	5150	5450			
			30 m.p.h.	lbs	6765	7370	8050	8550	9100	9650	10200	10500	11000	11400	1200			
20.5R25	UM3 E3/L3	193A2/177B**	10 Km/h	Kgs						8000	8250	8750	9000	9500	9750	10000	10300	10900
			5 m.p.h.	lbs						17600	18200	19300	19800	20900	21500	22000	22700	24000
			50 Km/h	Kgs	4000	4375	4750	5000	5450	5800	6000	6300	6700	6900	7300			
			30 m.p.h.	lbs	8800	9650	10500	11000	12000	12800	13200	13900	14800	15200	16100			
23.5R25	UM3 E3/L3	201A2/185B**	10 Km/h	Kgs						10300	10600	11200	11500	12150	12500	12850	13200	13600
			5 m.p.h.	lbs						22700	23400	24700	25400	26800	27600	28300	29100	30000
			50 Km/h	Kgs	5000	5450	6000	6300	6700	7300	7500	8000	8500	9000	9250			
			30 m.p.h.	lbs	11000	12000	13200	13900	14800	16100	16500	17600	18700	19800	20400			
26.5R25	UM3+ E3/L3	209A2/193B**	10 Km/h	Kgs						12850	13200	14000	14500	15000	15500	16000	16500	17000
			5 m.p.h.	lbs						28300	29100	30900	32000	33100	34200	35300	36480	37500
			50 Km/h	Kgs	6300	6900	7500	8000	8500	9000	9500	10000	10600	10900	11500			
			30 m.p.h.	lbs	13900	15200	16500	17600	18700	19800	20900	22000	23400	24000	25400			
29.5R25	UM3+ E3/L3	216A2/200B**	10 Km/h	Kgs						15500	16000	17000	17500	18000	19000	19500	20000	20600
			5 m.p.h.	lbs						34200	35300	37500	38600	39700	41900	43000	44100	45400
			50 Km/h	Kgs	7500	8250	9000	9500	10300	10900	11500	12150	12850	13200	14000			
			30 m.p.h.	lbs	16500	18200	19800	20900	22700	24000	25400	26800	28300	29100	30900			

SIZE	TYPE	RIM WIDTH		OUTSIDE DIAMETER	TYRE WIDTH	WIDTH LOADED	STATIC LOADED RADIUS	TREAD DEPTH
15.5R25	Tubeless	25-12.00/1.3	mm	1282.0	399.6	415	630	27.5
			in.	50.47	15.7	16.3	24.8	34/32
17.5R25	Tubeless	25-14.00/1.5	mm	1357.0	434.2	452	670	32.0
			in.	53.43	17.1	17.8	26.4	40/32
20.5R25	Tubeless	25-17.00/2.0	mm	1485.0	530.4	550	733	35.0
			in.	58.46	20.9	21.7	28.8	44/32
23.5R25	Tubeless	25-19.50/2.5	mm	1614.0	593.6	615	798	37.0
			in.	63.54	23.4	24.2	31.4	47/32
26.5R25	Tubeless	25-22.00/3.0	mm	1752.0	673	700	865	38.0
			in.	68.98	26.5	27.6	34.0	48/32
29.5R25	Tubeless	25-25.00/3.5	mm	1862.0	740.0	770	915	43.0
			in.	73.31	29.14	30.3	36.0	54/32

Maitech tyres conform to ETRTO, TRA & JATMA Standards.

Distributed by:

maitech®
ALL STEEL RADIAL

Uzmai International s.r.l. - Italy - Via Conche, 1151 - 37050 Isola Rizza VERONA
Tel. +39 045 6970505 Fax +39 045 6971377 - info@maitechtire.com - www.maitechtire.com