

BETTER BY DESIGN

**UM
HSS**



UM HSS

Exceptional Comfort

The non-directional tread design improves operator comfort by reducing road noise and delivering exact handling response.

On- and Off-Road Use

The aggressive, self-cleaning tread design provides excellent traction in tough, demanding applications.

High-speed Capabilities

Special HSS compound and small block tread design gives the UM-HSS high-speed capabilities.

UM HSS



maitech
ALL STEEL RADIAL

SIZE	PATTERN	LOAD INDEX - SPEED SYMBOL	SPEED	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (100 KPA=1BAR) AND SPEEDS									
				KPa	200	300	400	500	600	700	800	900	1000
				psi	29	44	58	73	87	102	116	131	145
385/95R24 (14.00R24)	UM HSS	170E	70 Km/h	Kgs	1800	2500	3050	3600	4100	4600	5050	5550	6000
			43 m.p.h.	lbs	3969	5513	6725	7938	9041	10143	11135	12238	13230
385/95R25 (14.00R25)	UM HSS	170E	70 Km/h	Kgs	1800	2500	3050	3600	4100	4600	5050	5550	6000
			43 m.p.h.	lbs	3969	5513	6725	7938	9041	10143	11135	12238	13230
445/95R25 (16.00R25)	UM HSS	174F	80 Km/h	Kgs				4270	4875	5480	6090	6700	
			50 m.p.h.	lbs				9416	10750	12084	13428	14773	

SIZE	TYPE	RIM WIDTH		OUTSIDE DIAMETER	TYRE WIDTH	WIDTH LOADED	STATIC LOADED RADIUS	TREAD DEPTH
385/95R24 (14.00R24)	Tubeless	24-10.00W	mm	1360	375	410	630	23
			in.	53.50	14.80	16.10	24.80	29/32
385/95R25 (14.00R25)	Tubeless	25-10.00/1.5	mm	1360	382	421	626	23
			in.	53.50	15.00	16.60	24.60	29/32
445/95R25 (16.00R25)	Tubeless	25-11.25/2.0	mm	1485	430	475	690	23
			in.	58.50	16.90	18.70	27.20	29/32

Maitech tyres conform to ETRTO, TRA & JATMA Standards.

Distributed by: _____

maitech
ALL STEEL RADIAL

Uzmai International s.r.l. - Italy - Via Conche, 1151 - 37050 Isola Rizza VERONA
Tel. +39 045 6970505 Fax +39 045 6971377 - info@maitechtire.com - www.maitechtire.com