

T2

Product name:

Operating limits:

Pressure: 28 Bar

Speed: 13 m/s

Temperature: -30°C... + 200°C



Specifications:

Type	d1	d3	d7	L1	L3
T2 3/8	9.525	28	24.6	33.7	8.7
T2 1/2	12.7	32	27.8	33.7	8.7
T2 5/8	15.875	35	30.95	35.3	10.3
T2 3/4	19.05	40	34.15	35.3	10.3
T2 7/8	22.225	43	37.3	35.3	10.3
T2 1	25.4	47	40.5	36.9	11.9
T2 1 1/8	28.575	56	47.65	44.9	11.9
T2 1 1/4	31.75	59	50.8	44.9	11.9
T2 1 3/8	34.925	63	54	44.9	11.9
T2 1 1/2	38.1	67	57.15	44.9	11.9
T2 1 5/8	41.275	71	60.35	44.9	11.9
T2 1 3/4	44.45	74	63.5	52.9	11.9
T2 1 7/8	47.625	77	66.7	52.9	11.9
T2 2	50.8	81	69.85	54.5	13.5
T2 2 1/8	53.97	84	73.05	54.5	13.5
T2 2 1/4	57.15	88	76.2	54.5	13.5
T2 2 3/8	60.32	91	79.4	54.5	13.5
T2 2 1/2	63.5	94	82.55	54.5	13.5

- ☐ Rotary Ring (Ceramic/SiC/TC)
- ☒ Stationary Ring (Carbon/SiC/TC)
- ☐ Secondary Ring (NBR/EPDM/VITON)
- ☒ Spring and Other Parts (SUS304/SUS316)

